

HIGHTEC SYNT RS DLS SAE 5W-30

High-performance engine oil developed specifically by BMW, Mercedes-Benz, Opel and VW for the requirements of the European market for models with exhaust after-treatment and turbocharging.

Description

HIGHTEC SYNT RS DLS SAE 5W-30 is a specially developed engine oil based on selected HC synthetic base oils for modern passenger car Otto and diesel engines with exhaust after-treatment (diesel particulate filters) and turbocharging.



Application

HIGHTEC SYNT RS DLS SAE 5W-30 has been developed specifically to meet the needs of modern petrol and diesel vehicles. It meets the requirements of many vehicle manufacturers and the ACEA C3 concerning a so-called low ash product. It is used in vehicles equipped with Otto and diesel engines, with or without exhaust after-treatment systems (DPF = Diesel Particulate Filter), according to the manufacturer's specification. It is therefore equally suitable for vehicles with or without turbocharging. In BMW vehicles, it is backward compatible with former specifications such as BMW LongLife-01/98. It covers the former specification GM-LL-A-025 or GM-LL-B-025 in Opel/GM vehicles.

Approvals

- BMW Longlife-04
- GM dexos2™ (Primary License No.: RB2D0113096)
- MB-Freigabe 229.31/229.51/229.52
- VW 505 00/505 01

The quality of this product is equivalent to EU regulations

- ACEA C2/C3
- API SN
- Opel OV0401547

Additionally this product is recommended when the following filling instructions are required

- API CF
- VW 502 00

Benefits

- First-class economy grade for multi-functional use in diesel and Otto engines from different manufacturers
- The low sulphated ash, low phosphorus and sulphur content protects diesel particulate filters and catalytic converters
- Hinders the formation of deposits in the engine. As a result, it guarantees first-rate operational safety performance and low maintenance costs.
- Low oil consumption due to a very low evaporation loss
- Good cold-starting properties and rapid engine lubrication
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of HIGHTEC SYNT RS DLS SAE 5W-30, a complete oil change is recommended.

Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.



20118 | 19.11.2019

HIGHTEC SYNT RS DLS SAE 5W-30

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,85
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	69
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	12
Viscosity index	ASTM D-7042	-	170
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	240
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36
CCS	ASTM D-5293	cP @ °C	5400 @ -30
Total base number	DIN 51639-1	mgKOH/g	7,2
HTHS	ASTM D4683	mPas	3,51

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Are you looking for the
correct oil for your vehicle?
Scan this code for the
ROWE-oilfinder.



20118 | 19.11.2019